

MINIMUM SAFETY REQUIREMENTS

The following list is provided by the CSA as a guide to regatta organizers of MINIMUM safety requirements for boats sailing in coastal races in the Caribbean. These requirements are intended as minimum standards and shall not supersede nor modify any of ISAF Racing Rules of Sailing Part 1- Fundamental Rules. It is further recommended that regattas utilize either [ISAF Offshore Special Regulations](#) or US Sailing [Safety Equipment Requirements](#).

These requirements are minimum standards and shall not supercede nor modify any of ISAF Racing Rules of Sailing for 2013-2016 PART 1- FUNDAMENTAL RULES or other requirements as set forth in the Notice of Regatta or Sailing Instructions.

1. Softwood plugs, or other suitable materials, tapered to fit into all thru hull fittings.
2. Lifelines and bow and stern pulpits, or lifelines secured in such a way as to form a stern pulpit, of not less than 18" in height, except lifelines may be split at the bow to facilitate sheeting. Lifelines shall be taut with not more than seven feet between supports, taut being defined as no apparent sag between supports. Lifelines shall be attached securely and in such a way that no part of the system is elastic in nature. With regard to hiking and the positioning of crew on the rail, the criteria of ISAF RRS 2013-2016 Part 4, Rule 49.2, must be met. This states that if the crew is required to hike with their upper bodies outside of the upper lifeline then both Upper and Lower Lifeline must be wire or single braided high modulus polyethylene. Lifeline Minimum Diameters, Required Materials and specifications shall comply with the corresponding specifications in the ISAF Offshore Special Regulations
3. Fire extinguisher, charged and in date, accessible from the deck.
4. Two buckets, of not less than two gallons capacity, fitted with lanyards of suitable strength and length.
5. One anchor with chain of suitable size for the boat's length and displacement with a suitable rode of at least 150 feet in length. No part of the anchor shall overhang the ends of the boat while racing.
6. A First Aid kit suitable for rendering First Aid treatment in minor emergencies.
7. Charts covering the area to be raced.
8. Lifejackets constructed to an accepted standard, for each person on board with a whistle attached. Lifejackets shall be of a suitable size for the intended wearer and be readily accessible.

9. One life ring capable of supporting the largest member of the crew in the water and positioned above deck such that it is immediately available for use in an emergency.
10. Heaving line at least 50 feet in length, capable of floating, positioned above deck such that it is immediately available for use in an emergency.
11. Three red hand flares and two orange smoke flares.
12. VHF radio capable of transmitting and receiving on emergency and race committee channels.
13. A compass suitable for navigation.
14. A shutoff valve, in working order, shall be fitted to each fuel tank.
15. Hatches, companionways, and ports shall be capable of being made watertight while racing.
16. Cockpits to be self-bailing and fitted with adequate drains.
17. Sufficient water shall be carried on board so that at the finish of a race there remains at least one pint per person.

CARIBBEAN SAILING ASSOCIATION
Copyright Caribbean Sailing Association 2013